




MARINE FENDERS INTERNATIONAL, INC.



- Ultra heavy-duty central steel core load distribution construction
- Available designs include Tee-Top, Pad Eye, Quick Release Hook(s), Bail eye, Hawse Pipe and other designs



- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam.
- Thick, tough filament nylon tire cord reinforced urethane skin.
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam.

Ocean Guard™ Pendant Buoys

Buoy Model PB#	Net Buoyancy		Diameter		Length		Height Overall		Buoy Weight		Working Load	
	lb.	kg	ft.	m.	ft.	m.	ft.	m.	lb.	kg.	lb.	kg.
PB-25-TT	5,513	2,500	4.5	1.37	6.8	2.06	7.1	2.17	1,286	583	150,000	330,750
PB-50-TT	11,025	5,000	5.6	1.70	8.4	2.55	8.2	2.50	1,979	898	150,000	330,750
PB-75-TT	16,538	7,500	6.3	1.93	9.5	2.90	9.0	2.73	2,614	1,185	150,000	330,750
PB-100-TT	22,050	10,000	7.0	2.12	10.5	3.19	10.2	3.10	3,415	1,549	150,000	330,750
PB-150-TT	33,075	15,000	7.9	2.42	11.9	3.63	11.1	3.40	4,561	2,068	150,000	330,750
PB-200-TT	44,100	20,000	8.7	2.66	13.1	3.98	12.2	3.72	5,882	2,668	200,000	441,000
PB-250-TT	55,125	25,000	9.4	2.86	14.1	4.29	12.9	3.93	7,055	3,200	200,000	441,000
PB-300-TT	66,150	30,000	9.9	3.03	14.9	4.55	13.4	4.10	8,100	3,673	200,000	441,000
PB-350-TT	77,175	35,000	10.5	3.19	15.7	4.78	14.0	4.25	9,134	4,142	250,000	551,250
PB-400-TT	88,200	40,000	10.9	3.34	16.4	5.01	14.7	4.49	10,780	4,889	250,000	551,250

* Actual values for above sizes may vary +/- 15% due to variations in materials, temperatures and tolerances.

Marine Fenders International, Inc.

• 909 Mahar Avenue • Wilmington • California • 90744 • USA

Telephone 1-310-834-7037 • Fax 1-310-834-7825 • E-mail: sales@marinefendersintl.com • www.marinefendersintl.com