



MARINE FENDERS INTERNATIONAL, INC.



- Ultra heavy-duty central steel core load distribution construction
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam



- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam
- Thick, tough filament nylon tire cord reinforced urethane skin

Ocean Guard™ Support Buoys

| Buoy Model SB # | Net Buoyancy | | Diameter | | Body Height | | Height Overall | | Safe Working Load | | Weight | |
|--------------------|--------------|-------|----------|-------|-------------|-------|----------------|-------|-------------------|--------|--------|-----|
| | lb | kg | in. | mm | in. | mm | in. | mm | lb. | kg. | lb. | kg. |
| SB-25 | 551 | 250 | 29 | 745 | 29 | 745 | 40 | 1,011 | 22,000 | 9,977 | 172 | 78 |
| SB-50 | 1,102 | 500 | 36 | 923 | 36 | 923 | 47 | 1,190 | 22,000 | 9,977 | 282 | 128 |
| SB-75 | 1,653 | 750 | 41 | 1,042 | 41 | 1,042 | 52 | 1,309 | 22,000 | 9,977 | 346 | 157 |
| SB-100 | 2,205 | 1,000 | 45 | 1,139 | 45 | 1,139 | 55 | 1,406 | 40,000 | 18,141 | 407 | 185 |
| SB-105 | 2,315 | 1,050 | 46 | 1,156 | 46 | 1,156 | 56 | 1,423 | 40,000 | 18,141 | 419 | 190 |
| SB-125 | 2,756 | 1,250 | 48 | 1,230 | 48 | 1,230 | 62 | 1,585 | 40,000 | 18,141 | 538 | 244 |
| SB-150 | 3,307 | 1,500 | 51 | 1,301 | 51 | 1,301 | 65 | 1,656 | 40,000 | 18,141 | 595 | 270 |
| SB-175 | 3,858 | 1,750 | 54 | 1,374 | 54 | 1,374 | 74 | 1,892 | 40,000 | 18,141 | 746 | 338 |
| SB-200 | 4,409 | 2,000 | 56 | 1,432 | 56 | 1,432 | 77 | 1,950 | 40,000 | 18,141 | 801 | 363 |
| SB-250 | 5,512 | 2,500 | 60 | 1,535 | 60 | 1,535 | 81 | 2,053 | 40,000 | 18,141 | 909 | 412 |
| SB-300 | 6,614 | 3,000 | 64 | 1,625 | 64 | 1,625 | 84 | 2,143 | 45,000 | 20,408 | 1,014 | 460 |
| SB-350 | 7,716 | 3,500 | 67 | 1,707 | 67 | 1,707 | 88 | 2,225 | 45,000 | 20,408 | 1,117 | 507 |
| SB-400 | 8,818 | 4,000 | 70 | 1,781 | 70 | 1,781 | 91 | 2,299 | 45,000 | 20,408 | 1,220 | 553 |
| SB-450 | 9,921 | 4,500 | 73 | 1,849 | 73 | 1,849 | 93 | 2,367 | 45,000 | 20,408 | 1,320 | 599 |
| SB-500 | 11,023 | 5,000 | 75 | 1,913 | 75 | 1,913 | 96 | 2,431 | 45,000 | 20,408 | 1,420 | 644 |
| SB-600 | 13,228 | 6,000 | 80 | 2,036 | 80 | 2,036 | 101 | 2,554 | 45,000 | 20,408 | 1,798 | 815 |
| SB-700 | 15,432 | 7,000 | 84 | 2,139 | 84 | 2,139 | 105 | 2,658 | 45,000 | 20,408 | 1,992 | 903 |

* Actual values for above sizes may vary +/- 15% due to variations in materials, temperatures and tolerances.

Marine Fenders International, Inc.

• 909 Mahar Avenue • Wilmington • California • 90744 • USA

Telephone 1-310-834-7037 • Fax 1-310-834-7825 • E-mail: sales@marinefendersintl.com • www.marinefendersintl.com