



MARINE FENDERS INTERNATIONAL, INC.



- Ultra heavy duty central steel core load distribution construction
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam



- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam
- Thick, tough filament nylon tire cord reinforced urethane skin

OCEAN GUARD SUPPORT BUOYS

BUOY MODEL	BUOYANCY NET		BUOY WEIGHT		DIAMETER OVERALL		HEIGHT OVERALL		WORKING LOAD	
	LBS	KG	LBS	KG	FT	M	FT	M	LB	TONS
SB-25	551	250	200	91	2.6	0.8	2.6	0.8	22,000	10
SB-50	1,102	500	385	175	3.2	1.0	3.2	1.0	22,000	10
SB-75	1,653	750	390	177	3.5	1.1	3.5	1.1	22,000	10
SB-100	2,205	1,000	640	290	4.0	1.2	4.0	1.2	40,000	18
SB-125	2,756	1,250	597	271	4.2	1.3	4.2	1.3	40,000	18
SB-150	3,307	1,500	730	331	4.5	1.4	4.5	1.4	40,000	18
SB-175	3,858	1,750	866	393	4.8	1.5	4.8	1.5	40,000	18
SB-200	4,409	2,000	980	445	5.0	1.5	5.0	1.5	40,000	18
SB-250	5,511	2,500	1,228	557	5.4	1.6	5.4	1.6	40,000	18
SB-300	6,614	3,000	1,285	583	5.6	1.7	5.6	1.7	45,000	20
SB-350	7,716	3,500	1,394	632	5.8	1.8	5.8	1.8	45,000	20
SB-400	8,818	4,000	1,500	680	6.0	1.8	6.0	1.8	45,000	20
SB-450	9,921	4,500	1,682	763	6.3	1.9	6.3	1.9	45,000	20
SB-500	11,023	5,000	1,897	860	6.5	2.0	6.5	2.0	45,000	20
SB-600	13,228	6,000	2,262	1,026	6.9	2.1	6.9	2.1	45,000	20
SB-700	15,432	7,000	2,640	1,198	7.3	2.2	7.3	2.2	45,000	20

* ACTUAL VALUES FOR ABOVE SIZES MAY VARY +/- 15% DUE TO VARIATIONS IN MATERIALS, TEMPERATURES AND TOLERANCES.